

AA-59569 Silver Plated Copper Tubular Braid



Made in compliance with MIL-SPEC QQ-B-575 (as revised). Braid is formed so as to maintain coverage of 90% shielding, (70% for 0.78 and smaller), over the nominal diameters specified.

Silver Plated: Individual wires are silver plated copper wires, conforming to ASTM B298 standard, with 40 micro inches minimum of silver plating. Excellent for use at temperatures exceeding 200°C or where special resistance to corrosion is required

Blake Part Number	Nominal Inside Diameter (inch)	AWG of Individual Ends	Carriers	# of Wires Per Strand	Total # of Individual Ends	Approximate AWG Equivalent	Approx. Current Carrying Cap. (amps)
BBD-10300T	0.031	36	24	1	24	22	7.0
BBD-10301T	0.062	36	24	2	48	19	11.0
BBD-10302T	0.062	34	16	2	32	19	11.0
BBD-10303T	0.062	32	16	1	16	20	9.0
BBD-10304T	0.078	36	24	3	72	18	16.0
BBD-10305T	0.109	36	24	4	96	16	19.0
BBD-10306T	0.109	34	16	4	64	16	19.0
BBD-10307T	0.109	32	16	2	32	17	18.0
BBD-10308T	0.125	36	24	5	120	15	25.0
BBD-10309T	0.125	34	24	3	72	16	19.0
BBD-10310T	0.125	32	24	2	48	15	25.0
BBD-10311T	0.156	36	24	10	240	12	40.0
BBD-10312T	0.171	36	24	7	168	14	32.0
BBD-10313T	0.171	34	24	5	120	13	36.0
BBD-10314T	0.171	32	24	3	72	14	32.0
BBD-10315T	0.203	36	24	13	312	11	46.0
BBD-10316T	0.203	34	24	8	192	11	46.0
BBD-10317T	0.203	32	24	5	120	11	46.0
BBD-10318T	0.250	36	24	16	384	10	53.0
BBD-10319T	0.281	30	24	5	120	9	60.0
BBD-10320T	0.375	36	48	8	384	10	53.0
BBD-10321T	0.375	34	48	5	240	10	53.0
BBD-10322T	0.375	32	48	3	144	11	46.0
BBD-10323T	0.375	30	24	7	168	8	75.0
BBD-10324T	0.437	30	24	10	240	6	90.0
BBD-10325T	0.500	36	48	11	528	9	62.0
BBD-10326T	0.500	34	24	7	336	9	62.0
BBD-10327T	0.500	32	48	4	192	9	62.0
BBD-10328T	0.500	30	48	15	360	5	120.0

AA-59569 Silver Plated Copper Tubular Braid



Made in compliance with MIL-SPEC QQ-B-575 (as revised). Braid is formed so as to maintain coverage of 90% shielding, (70% for 0.78 and smaller), over the nominal diameters specified.

Silver Plated: Individual wires are silver plated copper wires, conforming to ASTM B298 standard, with 40 micro inches minimum of silver plating. Excellent for use at temperatures exceeding 200°C or where special resistance to corrosion is required

Blake Part Number	Nominal Inside Diameter (inch)	AWG of Individual Ends	Carriers	# of Wires Per Strand	Total # of Individual Ends	Approximate AWG Equivalent	Approx. Current Carrying Cap. (amps)
BBD-10329T	0.562	30	48	10	480	3	145.0
BBD-10330T	0.656	30	48	16	768	1	190.0
BBD-10331T	0.781	36	48	18	864	7	88.0
BBD-10332T	0.781	34	48	11	528	7	88.0
BBD-10333T	0.781	32	48	7	336	7	88.0
BBD-10334T	0.875	30	48	7	336	5	100.0
BBD-10335T	1.000	30	48	8	384	4	120.0
BBD-10336T	1.125	30	48	9	432	4	130.0
BBD-10337T	1.375	30	48	11	528	3	150.0
BBD-10338T	1.500	30	48	12	576	2	165.0