

**M16878/16 or NEMA HP5 TYPE LX**



M16878/16 is a cross-linked polyethylene (PE) insulated general purpose electronic hook-up wire. This wire is commonly used in switchboards, panel boards, and distribution boards.

Conductor: Tin Plated Copper  
 Insulation: Cross-linked PE  
 Temp Rating: 125°C  
 Voltage Rating: 3000 Volts R.M.S.

Blake Part Number	AWG	Stranding	Diameter in Inches		Nom. O.D. (in)
			Min	Max	
BW-261LX-X	26	Solid	0.067	0.082	0.016
BW-267LX-X	26	7 x 34	0.070	0.085	0.019
BW-2619LX-X	26	19 x 38	0.070	0.085	0.020
BW-241LX-X	24	Solid	0.071	0.086	0.020
BW-247LX-X	24	7 x 32	0.075	0.090	0.024
BW-2419LX-X	24	19 x 36	0.075	0.090	0.025
BW-221LX-X	22	Solid	0.076	0.091	0.054
BW-227LX-X	22	7 x 30	0.081	0.098	0.030
BW-2219LX-X	22	19 x 34	0.081	0.098	0.032
BW-201LX-X	20	Solid	0.083	0.098	0.032
BW-207LX-X	20	7 x 28	0.089	0.105	0.038
BW-2019LX-X	20	19 x 32	0.089	0.105	0.040
BW-181LX-X	18	Solid	0.091	0.106	0.040
BW-187LX-X	18	7 x 26	0.099	0.114	0.048
BW-1819LX-X	18	19 x 30	0.099	0.114	0.050
BW-161LX-X	16	Solid	0.102	0.117	0.051
BW-1619LX-X	16	19 x 29	0.108	0.123	0.057
BW-1626LX-X	16	26 x 30	0.111	0.125	0.060
BW-141LX-X	14	Solid	0.115	0.130	0.064
BW-1419LX-X	14	19 x 27	0.123	0.138	0.072
BW-1219LX-X	12	19 x 25	0.127	0.142	0.091
BW-1237LX-X	12	37 x 28	0.156	0.171	0.089
BW-1265LX-X	12	65 x 30	0.153	0.168	0.093
BW-1037LX-X	10	37 x 26	0.174	0.189	0.111
BW-865LX-X	8	65 x 30	0.239	0.254	0.167
BW-6133LX-X	6	133 x 27	0.283	0.298	0.169
BW-4133LX-X	4	133 x 25	0.346	0.366	0.210
BW-2133LX-X	2	133 x 23	0.415	0.435	0.268
BW2665LX-X	2	665 x 30	0.415	0.435	0.355
BW1817LX-X	1	817 x 30	0.468	0.488	0.382
BW1/0259LX-X	1/0	259 x 24	0.518	0.538	0.424
BW1/01045LX-X	1/0	1045 x 30	0.518	0.538	0.431
BW2/01330LX-X	2/0	1330 x 30	0.575	0.599	0.475
BW3/01665LX-X	3/0	1665 x 30	0.657	0.681	0.535
BW4/02109LX-X	4/0	2109 x 30	0.790	0.733	0.600

X = Color: See Page BCC-1