

MIL-DTL-16878/19 TYPE DN



M16878/19 is a polyvinyl chloride (PVC) insulated general-purpose hook-up wire with a clear nylon jacket.

Conductor: Tin Plated Copper
 Insulation: PVC
 Jacket: Clear Nylon
 Temp Rating: 105°C
 Voltage Rating: 3000 Volts R.M.S.

Blake Part Number	AWG	Stranding	Nom. O.D. (in)	Nom. Insulation Thickness (in)	Jacket Thickness
BW-247DN-X	24	7 x 32	0.088	0.036	0.003
BW-2419DN-X	24	19 x 36	0.088	0.036	0.003
BW-227DN-X	22	7 x 30	0.094	0.036	0.003
BW-2219DN-X	22	19 x 34	0.094	0.036	0.003
BW-2019DN-X	20	19 x 32	0.101	0.036	0.003
BW-1819DN-X	18	19 x 30	0.112	0.036	0.003
BW-1619DN-X	16	19 x 29	0.121	0.036	0.003
BW-1419DN-X	14	19 x 27	0.136	0.036	0.003
BW-1219DN-X	12	19 x 25	0.170	0.036	0.003
BW-1037DN-X	10	37 x 26	0.193	0.036	0.003
BW-8133DN-X	8	133 x 29	0.257	0.036	0.003
BW-6133DN-X	6	133 x 27	0.303	0.036	0.003

X = Color: See Page BCC-1