

**M22759**

Mil-Spec	Insulation	Voltage	Temp.	Conductor	AWG Range	Cable Designator
SAE AS22759/5	Mineral Filled Extruded PTFE	600	200°C	SPC	24 THRU 4	VA
SAE AS22759/6	Mineral Filled Extruded PTFE	600	260°C	NPC	24 THRU 4	WA
SAE AS22759/7	Mineral Filled Extruded PTFE	600	200°C	SPC	24 THRU 4	SA
SAE AS22759/8	Mineral Filled Extruded PTFE	600	260°C	NPC	24 THRU 4	TA
SAE AS22759/9	Extruded PTFE	1000	200°C	SPC	28 THRU 8	LE
SAE AS22759/10	Extruded PTFE	1000	260°C	NPC	28 THRU 8	LH
SAE AS22759/11	Extruded PTFE	600	200°C	SPC	28 THRU 8	RC
SAE AS22759/12	Extruded PTFE	600	260°C	NPC	28 THRU 8	RE
SAE AS22759/16	Extruded ETFE	600	150°C	TPC	24 THRU 2/0	TE
SAE AS22759/18	Extruded ETFE	600	150°C	TPC	26 THRU 10	TG
SAE AS22759/32	XL ETFE	600	150°C	TPC	30 THRU 12	SB
SAE AS22759/33	XL ETFE	600	200°C	SP ALLOY	30 THRU 20	SC
SAE AS22759/34	XL ETFE	600	150°C	TPC	24 THRU 2/0	SD
SAE AS22759/35	XL ETFE	600	200°C	SP ALLOY	26 THRU 20	SE
SAE AS22759/41	XL ETFE	600	200°C	NPC	26 THRU 2/0	SM
SAE AS22759/42	XL ETFE	600	200°C	NP ALLOY	26 THRU 20	SN
SAE AS22759/43	XL ETFE	600	200°C	SPC	26 THRU 2/0	SP
SAE AS22759/44	XL ETFE	600	200°C	SPC	28 THRU 8	SR
SAE AS22759/45	XL ETFE	600	200°C	NPC	28 THRU 8	SS
SAE AS22759/46	XL ETFE	600	200°C	NP ALLOY	28 THRU 20	ST
SAE AS22759/80	Lightweight Composite	600	150°C	TPC	26 THRU 20	WB
SAE AS22759/81	Lightweight Composite	600	200°C	SP ALLOY	26 THRU 20	WC
SAE AS22759/82	Normal Weight Composite	600	260°C	NP ALLOY	26 THRU 20	WE
SAE AS22759/83	Normal Weight Composite	600	200°C	SPC	8 THRU 4/0	WF
SAE AS22759/84	Normal Weight Composite	600	260°C	NPC	8 THRU 4/0	WG
SAE AS22759/85	Normal Weight Composite	600	150°C	TPC	8 THRU 4/0	WH
SAE AS22759/86	Normal Weight Composite	600	200°C	SPC	26 THRU 4/0	WJ
SAE AS22759/87	Normal Weight Composite	600	260°C	NPC	26 THRU 4/0	WK
SAE AS22759/88	Normal Weight Composite	600	150°C	TPC	26 THRU 4/0	WL
SAE AS22759/89	Normal Weight Composite	600	200°C	SP ALLOY	26 THRU 20	WM
SAE AS22759/90	Normal Weight Composite	600	260°C	NP ALLOY	26 THRU 20	WN
SAE AS22759/91	Lightweight Composite	600	200°C	SPC	26 THRU 10	WP
SAE AS22759/92	Lightweight Composite	600	260°C	NPC	26 THRU 10	WR