

SAE AS22759/5



M22759/5 is insulated with extruded polytetrafluoroethylene (PTFE) reinforced with abrasion resistant mineral fillers. This provides excellent mechanical strength. Commonly used where extra abrasion resistance and good flexibility are required.

Conductor: Silver Plated Copper
 Insulation: Mineral Filled Extruded PTFE
 Temp Rating: 200°C
 Voltage Rating: 600 Volts R.M.S.
 M27500 Type: VA

Blake Part Number	AWG	Stranding	Insulation Diameter		LBS/MFT
			Min.	Max.	
BW-1530-X	24	19 x 36	0.070	0.080	6
BW-1540-X	22	19 x 34	0.080	0.090	8
BW-1550-X	20	19 x 32	0.090	0.100	10
BW-1560-X	18	19 x 30	0.105	0.115	14
BW-1570-X	16	19 x 29	0.120	0.130	18
BW-1580-X	14	19 x 27	0.136	0.150	25
BW-1590-X	12	19 x 25	0.153	0.167	34
BW-1500-X	10	37 x 26	0.172	0.186	48
BW-1508-X	8	133 x 29	0.241	0.255	84
BW-1506-X	6	133 x 27	0.290	0.310	126
BW-1504-X	4	133 x 25	0.340	0.370	188

X = Color: See Page BCC-1

SAE AS22759/6



M22759/6 is insulated with extruded polytetrafluoroethylene (PTFE) reinforced with abrasion resistant mineral fillers. This provides excellent mechanical strength. Commonly used where extra abrasion resistance and good flexibility are required.

Conductor: Nickel Plated Copper
 Insulation: Mineral Filled Extruded PTFE
 Temp Rating: 260°C
 Voltage Rating: 600 Volts R.M.S.
 M27500 Type: WA

Blake Part Number	AWG	Stranding	Insulation Diameter		LBS/MFT
			Min.	Max.	
BW-1630-X	24	19 x 36	0.070	0.080	6
BW-1640-X	22	19 x 34	0.080	0.090	8
BW-1650-X	20	19 x 32	0.090	0.100	10
BW-1660-X	18	19 x 30	0.105	0.115	14
BW-1670-X	16	19 x 29	0.120	0.130	18
BW-1680-X	14	19 x 27	0.136	0.150	25
BW-1690-X	12	19 x 25	0.153	0.167	34
BW-1600-X	10	37 x 26	0.172	0.186	48
BW-1608-X	8	133 x 29	0.241	0.255	84
BW-1606-X	6	133 x 27	0.290	0.310	126
BW-1604-X	4	133 x 25	0.340	0.370	188

X = Color: See Page BCC-1