

SAE AS22759/7



M22759/7 is insulated with extruded polytetrafluoroethylene (PTFE) reinforced with abrasion resistant mineral fillers. This provides excellent mechanical strength. Commonly used where extra abrasion resistance and good flexibility are required.

Conductor: Silver Plated Copper
 Insulation: Mineral Filled Extruded PTFE
 Temp Rating: 200°C
 Voltage Rating: 600 Volts R.M.S.
 M27500 Type: SA

Blake Part Number	AWG	Stranding	Insulation Diameter		LBS/MFT
			Min.	Max.	
BW-1630-X	24	19 x 36	0.060	0.064	6
BW-1640-X	22	19 x 34	0.071	0.075	8
BW-1650-X	20	19 x 32	0.080	0.084	10
BW-1660-X	18	19 x 30	0.090	0.094	14
BW-1670-X	16	19 x 29	0.099	0.105	18
BW-1680-X	14	19 x 27	0.112	0.118	19
BW-1690-X	12	19 x 25	0.131	0.137	29
BW-1600-X	10	37 x 26	0.154	0.162	42
BW-1608-X	8	133 x 29	0.215	0.225	73
BW-1606-X	6	133 x 27	0.264	0.276	111
BW-1604-X	4	133 x 25	0.321	0.450	169

SAE AS22759/8



M22759/8 is insulated with extruded polytetrafluoroethylene (PTFE) reinforced with abrasion resistant mineral fillers. This provides excellent mechanical strength. Commonly used where extra abrasion resistance and good flexibility are required.

Conductor: Nickel Plated Copper
 Insulation: Mineral Filled Extruded PTFE
 Temp Rating: 260°C
 Voltage Rating: 600 Volts R.M.S.
 M27500 Type: TA

Blake Part Number	AWG	Stranding	Insulation Diameter		LBS/MFT
			Min.	Max.	
BW-1730-X	24	19 x 36	0.060	0.064	4
BW-1740-X	22	19 x 34	0.071	0.075	6
BW-1750-X	20	19 x 32	0.080	0.084	8
BW-1760-X	18	19 x 30	0.090	0.094	11
BW-1770-X	16	19 x 29	0.099	0.105	14
BW-1780-X	14	19 x 27	0.112	0.118	19
BW-1790-X	12	19 x 25	0.131	0.137	29
BW-1700-X	10	37 x 26	0.154	0.162	42
BW-1708-X	8	133 x 29	0.215	0.225	73
BW-1706-X	6	133 x 27	0.264	0.276	111
BW-1704-X	4	133 x 25	0.321	0.450	169