

MIL-DTL-16878/2 TYPE C



M16878/2 is an electronic hook-up wire with containing a single layer of medium wall (.015") polyvinyl chloride (PVC) insulation. This wire is resistant to water, oil, acids, solvents and fungus and is commonly used for the internal wiring of electronic equipment.

Conductor: Coated Copper
 Insulation: PVC
 Temp Rating: 105°C
 Voltage Rating: 1000 Volts R.M.S.

Blake Part Number	AWG	Stranding	Nom. O.D. (in)	Nom. Insulation Thickness (in)	LBS/MFT
BW-261CU-X	26	Solid	0.054	0.016	2
BW-267CU-X	26	7 x 34	0.057	0.016	2
BW-2619CU-X	26	19 x 38	0.057	0.016	2
BW-241CU-X	24	Solid	0.058	0.016	3
BW-247CU-X	24	7 x 32	0.062	0.016	3
BW-2419CU-X	24	19 x 36	0.062	0.016	3
BW-221CU-X	22	Solid	0.064	0.016	4
BW-227CU-X	22	7 x 30	0.063	0.016	4
BW-2219CU-X	22	19 x 34	0.063	0.016	4
BW-201CU-X	20	Solid	0.070	0.016	5
BW-207CU-X	20	7 x 28	0.070	0.016	5
BW-2019CU-X	20	19 x 32	0.071	0.016	5
BW-181CU-X	18	Solid	0.079	0.016	8
BW-187CU-X	18	7 x 26	0.080	0.016	8
BW-1819CU-X	18	19 x 30	0.087	0.016	8
BW-161CU-X	16	Solid	0.089	0.016	11
BW-1619CU-X	16	19 x 29	0.092	0.016	11
BW-141CU-X	14	Solid	0.102	0.016	15
BW-1419CU-X	14	19 x 27	0.105	0.016	15
BW-1219CU-X	12	19 x 25	0.129	0.016	23

X = Color: See Page BCC-1