

**UL1007/1569**



UL1007 PVC insulated general purpose electronic hook-up wire resistant to water, oil, acids, solvents and fungus. May be used for the internal wiring of electronic equipment.

Conductor: Tinned Copper  
 Insulation: PVC  
 Temp Rating: 80°C  
 Voltage Rating: 300 Volts R.M.S.  
 Color Code: See Chart BCC-1

Blake Part Number	AWG	Stranding	Nom. O.D. (in)	Nom. Insulation Thickness (in)	LBS/MFT
BW-5200-X	30	7 x 38	0.043	0.41	1.41
BW-5210-X	28	7 x 36	0.047	0.41	1.60
BW-5220-X	26	7 x 34	0.051	0.41	2.00
BW-5229-X	26	Solid	0.057	0.41	1.80
BW-5230-X	24	7 x 32	0.057	0.41	2.80
BW-5239-X	24	Solid	0.065	0.41	2.40
BW-5240-X	22	7 x 30	0.065	0.41	3.70
BW-5249-X	22	Solid	0.071	0.41	3.30
BW-5250-X	20	10 x 30	0.071	0.41	4.80
BW-5259-X	20	Solid	0.080	0.41	4.60
BW-5260-X	18	16 x 30	0.080	0.41	7.00
BW-5269-X	18	Solid	0.095	0.41	6.70
BW-5270-X	16	26 x 30	0.095	0.41	10.50

X = Color: See Page BCC-1