

**UL1061**



UL1061 PVC insulated general purpose electronic hook-up wire resistant to water, oil, acids, solvents and fungus. May be used for the internal wiring of electronic equipment.

Conductor: Tinned Copper  
 Insulation: PVC  
 Temp Rating: 80°C  
 Voltage Rating: 300 Volts R.M.S.

Blake Part Number	AWG	Stranding	Nom. O.D. (in)	Nom. Insulation Thickness (in)	LBS/MFT
BW-5030-X	24	7 x 32	0.042	0.009	2.20
BW-5040-X	22	7 x 30	0.048	0.009	3.30
BW-5050-X	20	7 x 28	0.056	0.009	4.00
BW-5060-X	18	16 x 30	0.066	0.009	7.00
BW-5070-X	16	26 x 30	0.078	0.009	9.40

X = Color: See Page BCC-1

**UL1015**



UL1015 PVC insulated general purpose electronic hook-up wire resistant to water, oil, acids, solvents and fungus. May be used for the internal wiring of electronic equipment.

Conductor: Tinned Copper  
 Insulation: PVC  
 Temp Rating: 105°C  
 Voltage Rating: 600 Volts R.M.S.

Blake Part Number	AWG	Stranding	Nom. O.D. (in)	Nom. Insulation Thickness (in)	LBS/MFT
BW-5130-X	24	7 x 32	0.088	0.032	5.11
BW-5140-X	22	7 x 30	0.094	0.032	6.27
BW-5150-X	20	10 x 30	0.100	0.032	7.60
BW-5160-X	18	16 x 30	0.112	0.032	10.16
BW-5170-X	16	26 x 30	0.124	0.032	14.36
BW-5180-X	14	41 x 30	0.134	0.032	20.10
BW-5190-X	12	65 x 30	0.162	0.032	29.66
BW-5100-X	10	105 x 30	0.180	0.032	42.40

X = Color: See Page BCC-1