

**AMS-DTL-23053/8**



M23053/8 is a flame retardant, semi-rigid, irradiated Polyvinylidene Fluoride. It is a tough thin wall tubing with outstanding cut-through, abrasion, and heat resistance. M23053/8 has a shrink ratio of 50%, 2:1 and an operating temperature of -55°C to 175°C.

UL 224 VW-1  
MIL-DTL-23053/8  
AMS-3632  
CSA OFT  
RoHS Compliant

**Storage Life 5 Years**

Blake Part Number	Size in Inches	Expanded I.D. (in)	Recovered I.D. (in)	Nom. Recovered Wall Thickness (in)
BT-800-101-C	3/64	0.046	0.023	0.018
BT-800-102-C	1/16	0.063	0.031	0.018
BT-800-103-C	3/32	0.093	0.046	0.020
BT-800-104-C	1/8	0.125	0.062	0.020
BT-800-105-C	3/16	0.187	0.093	0.020
BT-800-106-C	1/4	0.250	0.125	0.025
BT-800-107-C	3/8	0.375	0.187	0.025
BT-800-108-C	1/2	0.500	0.250	0.025
BT-800-109-C	3/4	0.750	0.500	0.030
BT-800-110-C	1	1.000	0.750	0.035
BT-800-111-C	1 1/2	1.500	0.080	0.040

AMS-DTL-23053/8 is only available in Clear