


**AMS-DTL-23053/8**



M23053/8 is a flame retardant, semi-rigid, irradiated Polyvinylidene Fluoride. It is a tough thin wall tubing with outstanding cut-through, abrasion, and heat resistance. M23053/8 has a shrink ratio of 50%, 2:1 and an operating temperature of -55°C to 175°C.

UL 224 VW-1  
MIL-DTL-23053/8  
AMS-3632  
CSA OFT  
RoHS Compliant

**Storage Life 5 Years**

| Blake Part Number | Size in Inches | Expanded I.D. (in) | Recovered I.D. (in) | Nom. Recovered Wall Thickness (in) |
|-------------------|----------------|--------------------|---------------------|------------------------------------|
| BT-800-101-C      | 3/64           | 0.046              | 0.023               | 0.018                              |
| BT-800-102-C      | 1/16           | 0.063              | 0.031               | 0.018                              |
| BT-800-103-C      | 3/32           | 0.093              | 0.046               | 0.020                              |
| BT-800-104-C      | 1/8            | 0.125              | 0.062               | 0.020                              |
| BT-800-105-C      | 3/16           | 0.187              | 0.093               | 0.020                              |
| BT-800-106-C      | 1/4            | 0.250              | 0.125               | 0.025                              |
| BT-800-107-C      | 3/8            | 0.375              | 0.187               | 0.025                              |
| BT-800-108-C      | 1/2            | 0.500              | 0.250               | 0.025                              |
| BT-800-109-C      | 3/4            | 0.750              | 0.500               | 0.030                              |
| BT-800-110-C      | 1              | 1.000              | 0.750               | 0.035                              |
| BT-800-111-C      | 1 1/2          | 1.500              | 0.080               | 0.040                              |

AMS-DTL-23053/8 is only available in Clear