


AMS-3654 – LIGHT WEIGHT WALL



AMS-3654 is a light-weight walled tubing extruded from tetrafluoroethylene resin and is unsurpassed by any other tubing for use in applications for high temperatures and high frequencies. This tubing is rated for continuous operations of 250°C and retains its strength and flexibility throughout. This tubing is flexible, non-flammable, and resists fungus growth.

AMS-3654
 ASTM-3295
 UL Recognized
 RoHS Compliant

Blake Part Number	Nominal I.D. (in)	I.D. Min.	I.D. Max	Nominal Wall Thickness (in)
BTF-300-30-X	0.010	0.010	0.015	0.006
BTF-300-28-X	0.013	0.013	0.018	0.006
BTF-300-26-X	0.016	0.016	0.021	0.006
BTF-300-24-X	0.020	0.020	0.026	0.006
BTF-300-22-X	0.025	0.025	0.032	0.006
BTF-300-20-X	0.032	0.032	0.038	0.006
BTF-300-19-X	0.036	0.036	0.042	0.006
BTF-300-18-X	0.040	0.040	0.046	0.006
BTF-300-17-X	0.045	0.045	0.052	0.006
BTF-300-16-X	0.051	0.051	0.058	0.006
BTF-300-15-X	0.057	0.057	0.065	0.006
BTF-300-14-X	0.064	0.064	0.072	0.008
BTF-300-13-X	0.072	0.072	0.081	0.008
BTF-300-12-X	0.081	0.081	0.091	0.008
BTF-300-11-X	0.091	0.091	0.101	0.008
BTF-300-10-X	0.102	0.102	0.112	0.008
BTF-300-9-X	0.114	0.114	0.124	0.008
BTF-300-8-X	0.129	0.129	0.139	0.008
BTF-300-7-X	0.144	0.144	0.155	0.008
BTF-300-6-X	0.162	0.162	0.174	0.010
BTF-300-5-X	0.182	0.182	0.195	0.010
BTF-300-4-X	0.204	0.204	0.218	0.010
BTF-300-3-X	0.229	0.229	0.244	0.010
BTF-300-2-X	0.258	0.258	0.273	0.010
BTF-300-1-X	0.289	0.289	0.305	0.010
BTF-300-0-X	0.325	0.325	0.342	0.012

X = Color: See Page BCC-1