


AMS-3655 – THIN WALL



AMS-3655 is a thin walled tubing extruded from tetrafluoroethylene resin and is unsurpassed by any other tubing for use in applications for high temperatures and high frequencies. This tubing is rated for continuous operations of 250°C and retains its strength and flexibility throughout. This tubing is flexible, non-flammable, and resists fungus growth.

AMS-3655
ASTM-3295
UL Recognized
RoHS Compliant

Blake Part Number	Nominal I.D. (in)	I.D. Min.	I.D. Max	Nominal Wall Thickness (in)
BTF-250-30-X	0.010	0.010	0.015	0.009
BTF-250-28-X	0.013	0.013	0.018	0.009
BTF-250-26-X	0.016	0.016	0.021	0.009
BTF-250-24-X	0.020	0.020	0.026	0.010
BTF-250-22-X	0.025	0.025	0.032	0.010
BTF-250-20-X	0.032	0.032	0.038	0.012
BTF-250-19-X	0.036	0.036	0.042	0.012
BTF-250-18-X	0.040	0.040	0.046	0.012
BTF-250-17-X	0.045	0.045	0.052	0.012
BTF-250-16-X	0.051	0.051	0.058	0.012
BTF-250-15-X	0.057	0.057	0.065	0.012
BTF-250-14-X	0.064	0.064	0.072	0.012
BTF-250-13-X	0.072	0.072	0.081	0.012
BTF-250-12-X	0.081	0.081	0.091	0.012
BTF-250-11-X	0.091	0.091	0.101	0.012
BTF-250-10-X	0.102	0.102	0.112	0.012
BTF-250-9-X	0.114	0.114	0.124	0.015
BTF-250-8-X	0.129	0.129	0.139	0.015
BTF-250-7-X	0.144	0.144	0.155	0.015
BTF-250-6-X	0.162	0.162	0.174	0.015
BTF-250-5-X	0.182	0.182	0.195	0.015
BTF-250-4-X	0.204	0.204	0.218	0.015
BTF-250-3-X	0.229	0.229	0.244	0.015
BTF-250-2-X	0.258	0.258	0.273	0.015
BTF-250-1-X	0.289	0.289	0.305	0.015
BTF-250-0-X	0.325	0.325	0.342	0.015

X = Color: See Page BCC-1