

MIL-I-631



Expandable Sleeving products to a variety of industries. Expandable Sleeving offers an easy, affordable alternative to heat shrink tubing. This type of sleeving is convenient because it adjusts to fit comfortably over wire and cable components without heat-shrinking. This saves you the hassle of dealing with the extra hassle and cost of heat shrink equipment

Expandable Braided Polyester Sleeving
Operational Temp. Range -70°C to +125°C

Specifications
MIL-I-631

| General Purpose Blake Part Number | Flame Retardant Blake Part Number | Minimum Supplied I.D. (in) | Maximum Supplied I.D. (in) | Nominal Wall Thickness (in) |
|-----------------------------------|-----------------------------------|----------------------------|----------------------------|-----------------------------|
| BEBP-110-1/8 | BEBP-120-1/8 | 0.093 | 0.250 | 0.25 |
| BEBP-110-1/4 | BEBP-120-1/4 | 0.125 | 0.437 | 0.25 |
| BEBP-110-3/8 | BEBP-120-3/8 | 0.187 | 0.625 | 0.25 |
| BEBP-110-1/2 | BEBP-120-1/2 | 0.250 | 0.750 | 0.25 |
| BEBP-110-3/4 | BEBP-120-3/4 | 0.500 | 1.250 | 0.25 |
| BEBP-110-1 1/4 | BEBP-120-1 1/4 | 0.750 | 1.750 | 0.25 |
| BEBP-110-1 1/2 | BEBP-120-1 1/2 | 1.000 | 2.500 | 0.25 |
| BEBP-110-1 3/4 | BEBP-120-1 3/4 | 1.250 | 2.750 | 0.25 |
| BEBP-110-2 | BEBP-120-2 | 1.500 | 3.000 | 0.25 |
| BEBP-110-2 1/2 | BEBP-120-2 1/2 | 1.750 | 3.500 | 0.25 |