

MIL-I-3190/6



Expandable Sleeving products to a variety of industries. Expandable Sleeving offers an easy, affordable alternative to heat shrink tubing. This type of sleeving is convenient because it adjusts to fit comfortably over wire and cable components without heat-shrinking. This saves you the hassle of dealing with the extra hassle and cost of heat shrink equipment

Silicone Rubber Coated Fiber Glass Sleeving
Operational Temp. Rating 200°C
Operational Voltage Rating 600 Volts
Grade HA1

Specifications
MIL-I-3190/6

Blake Part Number	ASTM Size	M3190 Size	Inside Diameter (inches)		
			Nom.	Min.	Max.
BSRF946-24-X	24	0	.022	.020	.027
BSRF946-22-X	22	1	.027	.025	.032
BSRF946-20-X	20	2	.034	.032	.039
BSRF946-19-X	19	3	.038	.036	.044
BSRF946-18-X	18	4	.042	.040	.049
BSRF946-17-X	17	5	.047	.045	.055
BSRF946-16-X	16	6	.053	.051	.061
BSRF946-15-X	15	7	.059	.057	.066
BSRF946-14-X	14	8	.066	.064	.072
BSRF946-13-X	13	9	.076	.072	.080
BSRF946-12-X	12	10	.085	.081	.089
BSRF946-11-X	11	11	.095	.091	.101
BSRF946-10-X	10	12	.106	.102	.112
BSRF946-9-X	9	13	.118	.114	.124
BSRF946-8-X	8	14	.133	.129	.141
BSRF946-7-X	7	15	.148	.144	.158
BSRF946-6-X	6	16	.166	.162	.178
BSRF946-5-X	5	17	.186	.182	.198
BSRF946-4-X	4	18	.208	.204	.224
BSRF946-3-X	3	19	.234	.229	.249
BSRF946-2-X	2	20	.263	.258	.278
BSRF946-1-X	1	21	.294	.289	.311
BSRF946-0-X	0	22	.330	.325	.347
BSRF946-5/16-X	5/16	N/A	.313	.313	.334
BSRF946-3/8-X	3/8	23	.375	.375	.399
BSRF946-7/16-X	7/16	24	.438	.438	.462
BSRF946-1/2-X	1/2	25	.500	.500	.524
BSRF946-9/16-X	9/16	N/A	.563	.563	.585
BSRF946-5/8-X	5/8	26	.625	.625	.655
BSRF946-3/4-X	¾	27	.750	.750	.786
BSRF946-7/8-X	7/8	28	.875	.875	.911
BSRF946-1-X	1"	29	1.00	1.00	1.04

Available Colors

9 = White
N = Natural
0 = Black