

**M16878/14 or NEMA HP5 TYPE L**



M16878/14 is a cross-linked polyethylene (PE) insulated general purpose electronic hook-up wire. This wire is commonly used in switchboards, panel boards, and distribution boards.

Conductor: Tin Plated Copper  
 Insulation: Cross-linked PE  
 Temp Rating: 125°C  
 Voltage Rating: 600 Volts R.M.S.

Blake Part Number	AWG	Stranding	Diameter in Inches		Nom. O.D. (in)
			Min	Max	
BW-321L-X	32	Solid	0.024	0.030	0.008
BW-327L-X	32	7 x 40	0.026	0.032	0.010
BW-301L-X	30	Solid	0.026	0.032	0.010
BW-307L-X	30	7 x 38	0.028	0.034	0.012
BW-281L-X	28	Solid	0.029	0.035	0.013
BW-287L-X	28	7 x 36	0.031	0.037	0.015
BW-261L-X	26	Solid	0.032	0.038	0.016
BW-267L-X	26	7 x 34	0.035	0.041	0.019
BW-2619L-X	26	19 x 38	0.035	0.041	0.020
BW-241L-X	24	Solid	0.036	0.044	0.020
BW-247L-X	24	7 x 32	0.040	0.047	0.024
BW-2419L-X	24	19 x 36	0.040	0.047	0.025
BW-221L-X	22	Solid	0.041	0.050	0.025
BW-227L-X	22	7 x 30	0.046	0.053	0.030
BW-2219L-X	22	19 x 34	0.046	0.053	0.032
BW-201L-X	20	Solid	0.048	0.055	0.032
BW-207L-X	20	7 x 28	0.054	0.061	0.038
BW-2019L-X	20	19 x 32	0.054	0.061	0.040
BW-181L-X	18	Solid	0.056	0.064	0.040
BW-187L-X	18	7 x 26	0.064	0.071	0.048
BW-1819L-X	18	19 x 30	0.064	0.071	0.050
BW-161L-X	16	Solid	0.067	0.075	0.051
BW-1619L-X	16	19 x 29	0.073	0.081	0.057
BW-141L-X	14	Solid	0.080	0.088	0.064
BW-1419L-X	14	19 x 27	0.088	0.096	0.072

X = Color: See Page BCC-1