

M16878/15 or NEMA HP5 TYPE LL



M16878/15 is a cross-linked polyethylene (PE) insulated general purpose electronic hook-up wire. This wire is commonly used in switchboards, panel boards, and distribution boards.

Conductor: Tin Plated Copper
 Insulation: Cross-linked PE
 Temp Rating: 125°C
 Voltage Rating: 1000 Volts R.M.S.

Blake Part Number	AWG	Stranding	Diameter in Inches		Nom. O.D. (in)
			Min	Max	
BW-261LL-X	26	Solid	0.046	0.054	0.016
BW-267LL-X	26	7 x 34	0.049	0.057	0.019
BW-2619LL-X	26	19 x 38	0.049	0.057	0.020
BW-241LL-X	24	Solid	0.050	0.058	0.020
BW-247LL-X	24	7 x 32	0.054	0.062	0.024
BW-2419LL-X	24	19 x 36	0.054	0.062	0.025
BW-221LL-X	22	Solid	0.055	0.064	0.054
BW-227LL-X	22	7 x 30	0.060	0.068	0.030
BW-2219LL-X	22	19 x 34	0.060	0.068	0.032
BW-201LL-X	20	Solid	0.062	0.070	0.032
BW-207LL-X	20	7 x 28	0.068	0.076	0.038
BW-2019LL-X	20	19 x 32	0.068	0.076	0.040
BW-181LL-X	18	Solid	0.070	0.079	0.040
BW-187LL-X	18	7 x 26	0.076	0.086	0.048
BW-1819LL-X	18	19 x 30	0.076	0.086	0.050
BW-161LL-X	16	Solid	0.080	0.089	0.051
BW-1619LL-X	16	19 x 29	0.087	0.095	0.057
BW-1626LL-X	16	26 x 30	0.090	0.098	0.060
BW-141LL-X	14	Solid	0.094	0.103	0.064
BW-1419LL-X	14	19 x 27	0.102	0.110	0.072
BW-1219LL-X	12	19 x 25	0.121	0.129	0.091
BW-1237LL-X	12	37 x 28	0.119	0.127	0.089
BW-1265LL-X	12	65 x 30	0.123	0.131	0.093

X = Color: See Page BCC-1